




ISO COMPLIANT DISPLAY CARD

- One Time Password Function
- OATH compliance
- Fit for ISO card standard
- Durability
- Flexibility
- Power Efficiency
- Low cost and in mass production

DIMENSIONS



SPECIFICATIONS	
Property	Specification
Display Type	TN LCD (Black Digits and Light Gray Background)
Number of Digits	8
Supply Voltage	3.0 V
Battery Life	Up to 5 Years in event synchronous mode for 10 use/day
Durability & Flexibility	ISO7810 Compliant
Space Left for Embossed Characters (if combining with bank card application)	ISO7811/3 Compliant
Firmware Qualification	OATH Compliant / Event Sync
Operating Temperature	-10 C ~ 50 C
Storage Temperature	10 C ~ 30 C
Artwork of Card	Customizable
Production Status	Mass Production

APPLICATIONS
Secure Online Transaction VPN & WLAN & Intranets Access Control Physical Access Control Secure E-mail & Messaging

www.hierstar.com

US Headquarters

HisenseSoft Corp

151 Allegany Road
Stevensville, MD 21666, USA
Tel: 410-504-1865
Email: info@hisensesoft.com

US West Coast Office:

HisenseSoft Corp (HierStar)

Sacramento, CA 95683, USA
Tel: 916-354-8698
Email: rwilson@hisensesoft.com

China Headquarters

HierStar Ltd

C-2205 JinYuGuoJi,
48 Wang Jing Xi Road,
Chaoyang District,
Beijing, 100102, China
TEL: 010-64787346
FAX: 010-64787024
E-mail: info@hierstar.com