

2529													
Part Number	Packaging Options	Dimensions mm	Dimensions inches	Nominal Thickness	Maximum Thickness*	Formulation	Nominal Capacity**	Nominal Voltage	Pulse Capability	Operating Temperature	Storage Temperature	Attachment	Product Status
SF-2529-HT10EA037	TR / TT / BU	25 x 29	.98 x 1.14	.37 mm	.45 mm	HT	10 mAh	3.0 V	10 mA	-10C to 60C	-20C to 40C	Extended Tabs	Available
SF-2529-HT10BA037	TR / TT / BU	25 x 29	.98 x 1.14	.37 mm	.45 mm	HT	10 mAh	3.0 V	10 mA	-10C to 60C	-20C to 40C	Terminal Support	Available
SF-2529-HT14EA038	TR, TT or BU	25 x 29	.98 x 1.14	.38 mm	.45 mm	HT	14 mAh	3.0 V	14 mA	-10C to 60C	-20C to 40C	Extended Tabs	Samples Available
SF-2529-HT14BA038	TR, TT or BU	25 x 29	.98 x 1.14	.38 mm	.45 mm	HT	14 mAh	3.0 V	14 mA	-10C to 60C	-20C to 40C	Terminal Support	Samples Available

4823													
Part Number	Packaging Options	Dimensions mm	Dimensions inches	Nominal Thickness	Maximum Thickness*	Formulation	Nominal Capacity**	Nominal Voltage	Pulse Capability	Operating Temperature	Storage Temperature	Attachment	Product Status
SF-4823-HT18EA037	TR / TT / BU	48 x 23	1.89 x .91	.37mm	.45 mm	HT	18 mAh	3.0 V	18 mA	-10C to 60C	-20C to 40C	Extended Tabs	Available
SF-4823-HT18BA037	TR / TT / BU	48 x 23	1.89 x .91	.37mm	.45 mm	HT	18 mAh	3.0 V	18 mA	-10C to 60C	-20C to 40C	Terminal Support	Available
SF-4823-HT24EA038	TR, TT or BU	48 x 23	1.89 x .91	.38mm	.45 mm	HT	24 mAh	3.0 V	24 mA	-10C to 60C	-20C to 40C	Extended Tabs	Samples Available
SF-4823-HT24BA038	TR, TT or BU	48 x 23	1.89 x .91	.38mm	.45 mm	HT	24 mAh	3.0 V	24 mA	-10C to 60C	-20C to 40C	Terminal Support	Samples Available

7624													
Part Number	Packaging Options	Dimensions mm	Dimensions inches	Nominal Thickness	Maximum Thickness*	Formulation	Nominal Capacity**	Nominal Voltage	Pulse Capability	Operating Temperature	Storage Temperature	Attachment	Product Status
SF-7624-HT30EA037	TR / TT / BU	76 x 24	2.99 x .94	.37 mm	.45 mm	HT	30 mAh	3.0 V	30 mA	-10C to 60C	-20C to 40C	Extended Tabs	Available
SF-7624-HT30BA037	TR / TT / BU	76 x 24	2.99 x .94	.37 mm	.45 mm	HT	30 mAh	3.0 V	30 mA	-10C to 60C	-20C to 40C	Terminal Support	Available
SF-7624-LT30EA038	TR, TT or BU	76 x 24	2.99 x .94	.38 mm	.45 mm	LT	30 mAh	3.0 V	30 mA	-20C to 40C	-20C to 40C	Extended Tabs	Samples Available
SF-7624-LT30BA038	TR, TT or BU	76 x 24	2.99 x .94	.38 mm	.45 mm	LT	30 mAh	3.0 V	30 mA	-20C to 40C	-20C to 40C	Terminal Support	Samples Available
SF-7624-HT40EA038	TR, TT or BU	76 x 24	2.99 x .94	.38 mm	.45 mm	HT	40 mAh	3.0 V	40 mA	-10C to 60C	-20C to 40C	Extended Tabs	Samples Available
SF-7624-HT40BA038	TR, TT or BU	76 x 24	2.99 x .94	.38 mm	.45 mm	HT	40 mAh	3.0 V	40 mA	-10C to 60C	-20C to 40C	Terminal Support	Samples Available

BOLD	Available
	High Capacity
	Low Temperature

Packaging Options

TR	Tape and Reel Packaging
TT	Tray Packaging
BU	Bulk Packaging

* Max thickness is measured at the negative terminal insulator (highest point), see product data sheet for details.

** Nominal capacity at C/40 at 23°C

Formulation Legend

HT	High Temperature - designed to survive 135° C Lamination
LT	Low Temperature - designed to operate down to -20°C

Battery Attachment Legend

EA	Extended Tabs- Copper Anode Tab, Aluminum Cathode Tab
BA	Battery Terminal Support- Copper Anode Tab, Aluminum Cathode Tab

All product sheet specifications subject to change without notice.



Solicore, Inc. • 2700 Interstate Drive • Lakeland, FL 33805
 Phone: +1.863.603.7640 • Fax: +1.863.904.1479 • www.solicore.com

thin



flexible



safe

